



## Kane Ace™ M190

# Impact Modifier for Engineering Plastics (PC, SAN, ASA, Alloys)

#### PRODUCT DESCRIPTION

Kane Ace™ M190 is an impact modifier based on pure acrylic core-shell rubber particles, providing an excellent balance of impact resistance, modulus and viscosity with an extraordinary good weatherability and colorability.

#### **GENERAL BENEFITS**

- Gives high gloss and deep colours with pigments and particularly suitable for outdoor and colored applications
- Features excellent weatherability, and UV and heat stability that acrylics are well known for
- Improves the impact performance of engineering plastics, especially in polycarbonate blends at elevated temperatures and at temperatures of 0 °C and below

#### **TYPICAL APPLICATIONS**

- Automotive components: exterior components, headlight components, door and window hardware
- General industry goods: seat shells, office chair components, sports, garden and lawn components

#### **TYPICAL PROPERTIES**

<b>Chemical Description</b>	Acrylic Copolymer
Physical Form	fine white powder
Apparent spec. gravity	0,300 g/cc
<b>Volatile Matter Content</b>	≤ 1 %
Impact Strength	high

Note: please be aware that typical properties are approximate reference values. For guaranteed quality specifications, please contact us.

#### **OUALITY CONTROL**

Kaneka Belgium NV follows internationally recognized quality management principles. Our valid ISO certificates can be downloaded from our website.

EN ISO 9001: "Quality Management System" EN ISO 14001: "Environmental Management System" EN ISO 50001: "Energy Management System"

#### STORAGE AND HANDLING

Please consult the "General safety recommendations for the storage and handling of Kane Ace™ powders" and Safety Data Sheet for additional information concerning personal protective measures, safety, health and environmental information.

#### **SHELF LIFE GUARANTEE**

On condition that there is taken care about the conditions for storage(\*) as these are mentioned in the Safety Data Sheet and on the packaging itself of the Kane Ace™ product, Kane Ace™ M190 can be maintained in stock, keeping its characteristics, for a period up to three years after delivery date.

(\*) Store free, in original package. Store in cool area, do not store near heat sources. Store in dry well-ventilated area, avoid contact with moisture. Protect from light, especially from direct exposure to sunlight.



#### **REGULATORY INFORMATION**

Regulatory information is supplied upon request. Please contact info.regulatoryppd@kaneka.be

### HARMONIZED TARIFF CODE

39069090

#### **CAS NUMBER**

CAS number assigned to identify Kane Ace™ M190 is available upon request.

#### **PRODUCT PACKAGING**

Kane Ace<sup>™</sup> M190 is supplied in 10-kg bags [500 kg per pallet] and in 300-kg semi-bulk bags (600 kg per pallet).

#### **ADDITIONAL INFORMATION**

For additional information or specific recommendations for your intended application, please contact us.

## PERFORMANCE POLYMERS SOLUTIONS VEHICLE

**Technical Service Department** Phone: +32 (0) 14 25 78 37

Email: info.modifier@kaneka.be



#### Disclaimer

All information (including but not limited to technical statements, instructions, recommendations or suggestions) contained in this bulletin are for general information purposes only. The information is provided to the best of our knowledge and while we endeavour to keep the information up to date and correct according to the state of the art, we make no representations or warranties of any kind, express or implied, about the completeness, accuracy, reliability or suitability with respect to the information contained in this bulletin. Any reliance you place on such information is therefore strictly at your own risk. In no event will we be liable for any loss or damage (including, without limitation, indirect or consequential loss or damage, or any loss or damage whatsoever arising from loss of profits) arising out of, or in connection with, the use of this information and /or the use, handling, processing or storage of Kane Ace $^{\text{m}}$ .

#### **SUPPLIER**





