



# Kane Ace<sup>™</sup> M410 / Acrylic Impact Modifier

# **PRODUCT DESCRIPTION**

Kane Ace<sup>™</sup> M410 is an impact modifier based on pure acrylic core-shell rubber particles, providing an excellent balance of impact resistance, modulus and viscosity with an extraordinary good retention of heat distortion temperature.

#### **GENERAL BENEFITS**

- Improves the impact performance of engineering plastics, such as polyesters, polyamides and polycarbonate blends at elevated temperatures and at temperatures of 0 °C and below
- Features excellent weatherability and heat stability that acrylics are well known for
- Particularly suitable for outdoor and light-colored applications

# **TYPICAL APPLICATIONS**

- Automotive components: under-the-hood components, headlight components, door and window hardware
- Electrical components: cabinets, connectors, switches and reflector shells, body panels
- General industry goods: such as seat shells, office chair components, sports, garden and lawn components

# **TYPICAL PROPERTIES**

Chemical Description	Acrylic Copolymer
Physical Form	fine white powder
Bulk Density	0,51 g/cm <sup>3</sup>
Volatile Matter Content	0,5 %
Particle Size, d50	150 μm
Impact Strength	high

Note: please be aware that typical properties are approximate reference values. For guaranteed quality specifications, please contact us.

# **QUALITY CONTROL**

Kaneka Belgium NV follows internationally recognized quality management principles. Our valid ISO certificates can be downloaded from our website.

EN ISO 9001: "Quality Management System" EN ISO 14001: "Environmental Management System" EN ISO 50001: "Energy Management System"

#### **STORAGE AND HANDLING**

Please consult the **"General safety recommenda-tions for the storage and handling of Kane Ace™powders"** and **Safety Data Sheet** for additional information concerning personal protective measures, safety, health and environmental information.

#### SHELF LIFE GUARANTEE

On condition that there is taken care about the conditions for storage(\*) as these are mentioned in the Safety Data Sheet and on the packaging itself, Kane Ace<sup>™</sup> M410 can be maintained in stock, keeping its characteristics, for a period up to three years after delivery date.

(\*) Store free, in original package. Store in cool area, do not store near heat sources. Store in dry well-ventilated area, avoid contact with moisture. Protect from light, especially from direct exposure to sunlight.



#### **REGULATORY INFORMATION**

Regulatory information is supplied upon request. Please contact info.regulatoryppd@kaneka.be

# HARMONIZED TARIFF CODE

39069090

#### **CAS NUMBER**

CAS number assigned to identify Kane Ace<sup>™</sup> M410 is available upon request.

#### **PRODUCT PACKAGING**

Kane Ace<sup>™</sup> M410 is supplied in 25-kg bags [750 kg per pallet] and in 500-kg semi-bulk bags [1000 kg per pallet].

#### **ADDITIONAL INFORMATION**

For additional information or specific recommendations for your intended application, please contact us. **PERFORMANCE POLYMERS SOLUTIONS VEHICLE Technical Service Department** 

Phone: +32 (0) 2 663 01 89 Email: info.modifier@kaneka.be



#### Disclaimer

All information (including but not limited to technical statements, instructions, recommendations or suggestions) contained in this bulletin are for general information purposes only. The information is provided to the best of our knowledge and while we endeavour to keep the information up to date and correct according to the state of the art, we make no representations or warranties of any kind, express or implied, about the completeness, accuracy, reliability or suitability with respect to the information contained in this bulletin. Any reliance you place on such information is therefore strictly at your own risk. In no event will we be liable for any loss or damage (including, without limitation, indirect or consequential loss or damage, or any loss or damage whatsoever arising from loss of profits) arising out of, or in connection with, the use of this information and /or the use, handling, processing or storage of Kane Ace<sup>™</sup>.

SUPPLIER KANEKA BELGIUM NV Nijverheidsstraat 16, B - 2260 Westerlo, BELGIUM www.kaneka.be

